

## LED-RL21A (-22A)



LM79

LM80

### Product Description

- ▶ High-pressure die cast aluminum housing with powder-coated finish for corrosion resistance
- ▶ High quality polycarbonate (PC) lens optimizes lumen output
- ▶ Heat-resistant and gas tight rubber seal for high IP rating
- ▶ IP Class: IP65


### Application

Parks, Shopping Malls, Courtyards, Historic Areas, Pedestrian path etc.



| Model | Input Power | Delivered Lumens (5000K) | ETL | DLC     | Replaces     | Input Voltage       | CCT (K)      | CRI | Power Factor | THD  | Installation                         |
|-------|-------------|--------------------------|-----|---------|--------------|---------------------|--------------|-----|--------------|------|--------------------------------------|
| RL21A | 40W         | 4,800LM                  | ✓   |         | 100-150W HID | 120-277V<br>50/60HZ | 4000<br>5000 | >75 | >0.92        | <15% | Φ 2.36-3.05"<br>(Φ 60-78) Round pole |
|       | 60W         | 7,200LM                  | ✓   | Pending | 150-250W HID |                     |              |     |              |      |                                      |
|       | 80W         | 8,800LM                  | ✓   |         | 250-400W HID |                     |              |     |              |      |                                      |
| RL22A | 120W        | 15,500LM                 | ✓   |         | 400-600W HID | 120-277V<br>50/60HZ | 4000<br>5000 | >75 | >0.92        | <15% | Φ 2.36-3.05"<br>(Φ 60-78) Round pole |
|       | 150W        | 18,500LM                 | ✓   |         | 600-750W HID |                     |              |     |              |      |                                      |

Inch(mm)



### Distribution Curve Flux

