

Integra:ENERGY

POWER SELECTABLE

EVC Level 2, 48A Series

Specifications:

Model Number	EVC/A48S/J18/EG/5D
Input Current	48/40/32/16A
Input Voltage (Single phase)	200-240V / 60Hz
Network Connectivity	Ethernet + 4G
RFID+QR Code	Included
Credit Card	Optional
Local Load Management	Optional
OTA Technology	Included
Plug	SAE J1772 Type 1
Number of Port	Single
Charging Cable	18 ft
OCPP 1.6	Yes
Open ADR 2.0b Compliant	N/A
CTEP	Yes
AC Input Connection	L/N/GND
Max Output, 60 Hz	48A / 11.5kW
Hardwired	Yes
Dimensions (H x W x D)	13.8 x 9.8 x 5.1 inch
Weight (Lbs)	18.1 Lbs
IP Protection	IP65 for Charger; IP54 for cable NEMA 3
Tamper Resistant	IK08, except LCD & RFID
Cable Management	Optional
Operating Temperature	-22 to 122 °F
Humidity	Max 85%
Metering Accuracy	+/- 1%
Input Protection	UVP, OVP, RCD, SPD
Output Protection	OCP, Control Pilot Fault
Internal Protection	OTP, MCU function fault
Safety	UL2594, UL2231-1/-2
FCC compliant	Yes
Energy Star Certified	Yes
Power Configurable	Built-in
LCD Display	5-inch LCD Display



*Cable Hook Included



IEV48PSPD



IEV48PDPP



IEV48PDPP-CR

745 Albany Shaker Rd
Latham, New York 12110
P: 855.270.3107 | IntegraEnergy.com